



Ficha de producto / *Datasheet* » CRD48

Características generales / *Main features*

COMPATIBILIDAD / *COMPATIBILITY*

Gama CR / CR range

CAPACIDAD / *CAPACITY*

4 conectores* RJ45 / *84RJ45 connectors**

* Conectores tipo Keystone 19,4mm, Keystone 20,4mm o Systimax / *19.4mm Keystone connectors, Keystone 20,4mm or Systimax.*

ACABADO / *COLOR RANGE*

/6 - Grafito RAL 7021 / *6 - Graphite RAL 7021*

COMPOSICIÓN / *COMPONENTS*

Cubeta / *box*

Laterales(4ud) / *Sides (4ud)*

Tapa / *cover*

Tornillería tapa(4ud) / *Cover screws(4ud)*

Tornillería montaje suelo x4 / *floor mount screws*

Características técnicas/*technical features*

INSTALACIÓN /*INSTALLATION*

Suelo/*Floor*

Techo/*Cieling*

NORMATIVAS/ *APPROVALS*

UNE-EN- 60670

Marcado CE / *CE marking*

MATERIA PRIMA/ *RAW MATERIALS*

Polycarbonato libre de halógenos / *Halogen free polycarbonate*

MEDIDAS / *SIZE (mm)*

	Alto/ <i>Height</i>	Largo/ <i>Length</i>	Ancho/ <i>Width</i>
CRDX	45	130	190

